

G50 LED DOWNLIGHT MODULE

LED Downlight Module System



Patented



Feature

- The G50 module fits our custom mounting rings and are adaptable to fit most existing halogen MR-16 type fittings
- Anti-glare reflector with 3 beam angles, which directly replicates Mr16 halogen beam angles
- Miniature in size and thermal management provides great flexibility to suit a wide variety of applications
- Aesthetic pleasing design
- Delivers equivalent light output to a **35W halogen**
- 3 Year Warranty
- IPART Approved
- IP44

Temperature

- Ambient operating temperature: -20°C~+40°C
- Storage temperature: -30°C~+60°C

G50 SPECIFICATION

Replace Halogen 35W




G50 downlight module is equivalent to 35W MR16 halogen

600 Lm ~ 650 Lm MODELS

Item No	Product Code	Downlight output	CD	LED Power	System Power	CRI	CCT	LED Brand
07914	LED-EVO-G50-22-3K	600 lm	2382 cd	6 W	8 W	83	3000K	LUMINUS
07919	LED-EVO-G50-22-4K	650 lm	2587 cd	6 W	8 W	83	4000K	LUMINUS
07804	LED-EVO-G50-36-3K	600 lm	1500 cd	6 W	8 W	83	3000K	LUMINUS
07806	LED-EVO-G50-36-4K	650 lm	1619 cd	6 W	8 W	83	4000K	LUMINUS
07805	LED-EVO-G50-60-3K	600 lm	868 cd	6 W	8 W	83	3000K	LUMINUS
07807	LED-EVO-G50-60-4K	650 lm	943 cd	6 W	8 W	83	4000K	LUMINUS

Housing: aluminium with nickel coated
Reflector: PC with AL plating
Safety Glass coated with high transmittance film
Weight: 85g



LED Driver :
External Driver (CE/CB certified)
Mains Dim: standard

